

Electrical Characteristics									
Family		SB							
Number of poles		1P - 2P - 3P - 4P							
Frame size		Frame size 1			Frame size 2		Frame size 3		
Thermal current I _{th} (40°C)		16A	25A	32A	40A	63A	80A	100A	125A
Operational frequency		50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Rated insulation voltage (U _i)		500 V	500 V	500 V	500 V	500 V	500 V	500 V	500 V
Rated impulse with-stand voltage U _{imp}		3 KV	3 KV	3 KV	6 KV	6 KV	6 KV	6 KV	6 KV
Protection degree		2	2	2	3	3	3	3	3
Working temperature		-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C	-20 to 50°C
Storage temperature		-40 to 80°C	-40 to 80°C	-40 to 80°C	-40 to 80°C	-40 to 80°C	-40 to 80°C	-40 to 80°C	-40 to 80°C
Operational Currents I _e									
Rated voltage	Load duty category								
400V AC	AC 21A	16A	25A	32A	40A	63A	80A	100A	125A
400V AC	AC 22B	16A	25A	32A	40A	63A	80A	100A	125A
400V AC	AC 22A	16A	25A	32A	40A	63A	80A	100A	125A
400V AC	AC 23A	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA
Short circuit characteristic									
Rated short time with-stand current 1s I _{cs} (rms)	IEC 60947-3	480A / 1sec			945A / 1 sec		1500A / 1sec		
Prospective short circuit current (rms)	EN 60669	3kA	3kA	3kA	6kA	6kA	n/a	n/a	n/a
Associated fuse links (gG)		16A	25A	32A	40A	63A	n/a	n/a	n/a
Mechanical characteristic									
Rigid cable section		16 mm ²	16 mm ²	16 mm ²	25 mm ²	25 mm ²	50 mm ²	50 mm ²	50 mm ²
flexible cable section		10 mm ²	10 mm ²	10 mm ²	16 mm ²	16 mm ²	35 mm ²	35 mm ²	35 mm ²
Tightening torque		1.8 Nm	1.8 Nm	1.8 Nm	2.8 Nm	2.8 Nm	3.6 Nm	3.6 Nm	3.6 Nm
IP protection degree		20	20	20	20	20	20	20	20
Mechanical endurance (number of cycle)		100,000	100,000	100,000	30,000	30,000	20,000	20,000	20,000
Electrical endurance @ AC22 (number of cyles)		25,000	25,000	25,000	5,000	5,000	2,500	2,500	2,500
Overall dimension									
Width (mm)	1P	17.5	17.5	17.5	17.5	17.5	17.5	17.5	17.5
	2P	17.5	17.5	17.5	35	35	35	35	35
	3P	35	35	35	52.5	52.5	52.5	52.5	52.5
	4P	35	35	35	70	70	70	70	70
Height (mm)		83	83	83	83	83	83	83	83
Depth (mm)		72	72	72	72	72	72	72	72