

STANDARD | 24 V DC

PDV24

24 V ■ 19 W

NON ÉTANCHE

Dimensions : 138 x 40 x 28,5 mm



RÉF. **RUBAL2415**

BRICK100

24 V ■ 100 W

Étanche 💧 IP 67

Dimensions : 100 x 77 x 22 mm



RÉF. **RUBAL24100IP**

FB30

24 V ■ 30 W

NON ÉTANCHE

Dimensions : 117 x 75 x 20 mm



RÉF. **RUBAL2430**

BRICK150

24 V ■ 150 W

Étanche 💧 IP 67

Dimensions : 100 x 77 x 29 mm



RÉF. **RUBAL24150IP**

MD70

24 V ■ 70 W

NON ÉTANCHE

Dimensions : 206 x 51 x 36 mm



RÉF. **MD70**


MB300

24 V ■ 300 W

Étanche 💧 IP 65

NON ÉTANCHE

Dimensions : 152 x 104 x 46 mm



RÉF. **RUBALIMIP24**

MD100

24 V ■ 100 W

NON ÉTANCHE

Dimensions : 206 x 51 x 36 mm



RÉF. **RUBAL24100**

NT110

Boîtier interface

DALI / 1-10V / PUSH

NON ÉTANCHE

Dimensions : 138 x 40 x 28,5 mm



RÉF. **NT110**

PBOX150

24 V ■ 150 W

NON ÉTANCHE

Dimensions : 207 x 76 x 35 mm



RÉF. **PB15024**

P110

Potentiomètre 1-10V

NON ÉTANCHE

Dimensions : 32 x 20 x 15 mm



RÉF. **P110**