

STANDARD | 24 V DC

PDV24

24 V ■ 19 W

NON ÉTANCHE

Dimensions : 138 x 40 x 28,5 mm



RÉF. RUBAL2415

MD200

24 V ■ 200 W

NON ÉTANCHE, dimensions : 207 x 76 x 35 mm



RÉF. RUBAL24200

FB30

24 V ■ 30 W

NON ÉTANCHE

Dimensions : 117 x 75 x 20 mm



RÉF. RUBAL2430

BRICK100

24 V ■ 100 W

Étanche  IP 67

Dimensions : 100 x 77 x 22 mm



RÉF. RUBAL24100IP

MD70

24 V ■ 70 W

NON ÉTANCHE

Dimensions : 206 x 51 x 36 mm



RÉF. MD70

BRICK150

24 V ■ 150 W

Étanche  IP 67

Dimensions : 100 x 77 x 29 mm



RÉF. RUBAL24150IP

MD100

24 V ■ 100 W

NON ÉTANCHE

Dimensions : 206 x 51 x 36 mm



RÉF. RUBAL24100

NT110

**Boîtier interface
DALI / 1-10V / PUSH**

NON ÉTANCHE

Dimensions : 138 x 40 x 28,5 mm



RÉF. NT110

PBOX150

24 V ■ 150 W

NON ÉTANCHE

Dimensions : 207 x 76 x 35 mm



RÉF. PB15024

P110

Potentiomètre 1-10V

NON ÉTANCHE

Dimensions : 32 x 20 x 15 mm



RÉF. P110