

Lampe LED flamme et sphérique



L5E14FL27K

L5B22FL27K

L5E27FL27K

L5E14SP27K

L5B22SP27K

L5E27SP27K



LES + PRODUITS

- Lampe LED SMD
- 2700 K / 4000 K
- Allumage instantané
- t° de fonctionnement :
- 20 °C à + 40 °C



Référence	W	Culot	Lumens	Temp. couleur	Forme	IRC	Durée de vie	Dimensions Ø x ht (mm)	UE	Carton
L5E14FL27K	5	E14	350 lm	2700 K	Flamme C35	80	25 000 h	35 x 105	1	6
L6E14FL27K	6	E14	470 lm	2700 K	Flamme C35	80	25 000 h	35 x 105	1	6
L6E14FL27KD	6	E14	470 lm	2700 K	Flamme C35	80	25 000 h	35 x 105	1	6
L6E14FL4K	6	E14	470 lm	4000 K	Flamme C35	80	25 000 h	35 x 105	1	6
L7E14FL27K	7	E14	810 lm	2700 K	Flamme C35	80	25 000 h	38 x 115	1	6
L5B22FL27K	5	B22	330 lm	2700 K	Flamme C35	80	25 000 h	35 x 105	1	6
L5E27FL27K	5	E27	330 lm	2700 K	Flamme C35	80	25 000 h	35 x 105	1	6
L5E14SP27K	5	E14	350 lm	2700 K	SPH A40	80	25 000 h	41 x 80	1	6
L6E14SP27K	6	E14	470 lm	2700 K	SPH A40	80	25 000 h	41 x 80	1	6
L6E14SP27KD	6	E14	470 lm	2700 K	SPH A40	80	25 000 h	41 x 80	1	6
L6E14SP4K	6	E14	470 lm	4000 K	SPH A40	80	25 000 h	41 x 80	1	6
L6E27SP27KD	6	E27	470 lm	2700 K	SPH A40	80	25 000 h	41 x 80	1	6
L5B22SP27K	5	B22	330 lm	2700 K	SPH A40	80	25 000 h	41 x 80	1	6
L5E27SP27K	5	E27	330 lm	2700 K	SPH A40	80	25 000 h	41 x 87	1	6

 = version dimmable