


Lampe linolite LED S19



Référence	W	Culot	Lumens	Temp. couleur	Forme	Angle	IRC	Durée de vie	Dimensions Ø x H (mm)	UE	Carton
L7S1927K	7	S19	600 lm	2700 K	Linolite	300°	80	25 000 h	38 x 310	I	4/72
L7S194K	7	S19	600 lm	4000 K	Linolite	300°	80	25 000 h	38 x 310	I	4/72
L9S1927K	9	S19	900 lm	2700 K	Linolite	300°	80	25 000 h	38 x 310	I	4/72
L9S194K	9	S19	900 lm	4000 K	Linolite	300°	80	25 000 h	38 x 310	I	4/72

Lampe LED R7S



Référence	W	Culot	Lumens	Temp. Couleur	Angle	IRC	Durée de vie	Dimensions Ø x H (mm)	UE	Carton
L4R7S78/27K	4,5	R7S	470	2700 K	360°	80	15 000 h	25 x 78	I	6
L4R7S78/4K	4,5	R7S	470	4000 K	360°	80	15 000 h	25 x 78	I	6
L10R7S118/27K	9,8	R7S	1200	2700 K	360°	80	15 000 h	25 x 118	I	6
L10R7S118/4K	9,8	R7S	1200	4000 K	360°	80	15 000 h	25 x 118	I	6
L16R7S118/27K	16	R7S	2100	2700 K	360°	80	25 000 h	25 x 118	I	6
L16R7S118/4K 	16	R7S	2100	4000 K	360°	80	25 000 h	25 x 118	I	6

 = version dimmable

Cliquez sur le produit et laissez-vous guider 

LUXNA

SOURCES LED • 27

SOURCES
LED

SOURCES
FLUO

LAMPES
À DÉCHARGE

ÉCLAIRAGE
TECHNIQUE

ÉCLAIRAGE
RÉSIDENTIEL

ÉCLAIRAGE
FONCTIONNEL

ÉCLAIRAGE
EXTÉRIEUR

ACCESSOIRES ET
ALIMENTATIONS